

KONGIA Pre-Terminated SC/UPC to SC/UPC OS2 Duplex Coiled Fiber Optic Patch Cord

Fiber Optics / Fiber Optic Patch Cords

SC/UPC to SC/UPC · OS2 single-mode G.652D 9/125 µm · Coiled duplex · LSZH · 2.0 mm · 50 m · 100 m · 150 m · 200 m · 300 m.



FIBRA ÓPTICA PRETERMINADA
50 m · OS2 · Duplex
SC/UPC ↔ SC/UPC
LSZH · 2.0 mm · 2 fibras
KG-FO-PT-SCU-SCU-OS2-DX-050M

KG-FO-PT-SCU-SCU-OS2-DX

Connector A
SC/UPC

Connector B
SC/UPC

Fiber type
OS2 single-mode G.652D 9/125 µm

Key features

- SC/UPC and SC/UPC connectors
- OS2 single-mode G.652D 9/125 µm · 2 fibers
- Yellow LSZH jacket · Diameter: 2.0 mm
- Supplied directly coiled, without a reel
- Available lengths: 50 m · 100 m · 150 m · 200 m · 300 m

Technical specifications

Parameter	Specification
Model	KG-FO-PT-SCU-SCU-OS2-DX
Connector A	SC/UPC
Connector B	SC/UPC
Fiber type	OS2 single-mode G.652D 9/125 µm
Construction	Coiled duplex
Fiber count	2

Technical specifications

Parameter	Specification
Available lengths	50 m · 100 m · 150 m · 200 m · 300 m
Jacket color	Yellow
Jacket material	LSZH
Cable diameter	2.0 mm
Pack size	Directly coiled, without a reel
Interface compatibility	Select the same fiber type, connector and polish as the equipment ports
Warranty	5 years

Applications

Pre-terminated links between equipment

Connection of two points using an assembly with connectors at both ends, selected according to the project route.

Single-mode enterprise networks

Organization of optical links, checking that each end matches the equipment's connector and polish.

Optical transmission and reception channels

Two fibers to connect Tx and Rx ports. Check end-to-end polarity before commissioning the link.

Cable maintenance and reorganization

Jumper replacement and connection reorganization using suitable lengths, keeping connectors clean and avoiding tight bends.

Integration in telecommunications projects

Assembly selection by interface, fiber and length. For exposed routes or special raceways, confirm the required jacket before selecting the cable.

Packaging & contents

1 pre-terminated assembly supplied directly coiled, without a reel. Length according to the selected option.

Warranty

KONGIA 5-year warranty.

Declared compliance

RoHS · ISO 9001 · REACH · CE Compliant