1.25 mm One-Click Fiber Connector Cleaner

Fiber Optics / Fiber Optic Tools

Manual dry cleaner for 1.25 mm ferrules and LC / MU connectors. Its antistatic resin body includes an extendable rod, a tape inspection window and a protective cap with a transparent tether. Offers more than 800 nominal cleaning operations.

KG-FT-CLN-1.25

Type
One-Click dry cleaner

Ferrule
1.25 mm

Connectors
LC / MU

Key features

- Compatible with LC / MU ferrules of 1.25 mm.
- More than 800 nominal dry cleaning operations.
- Extendable rod to facilitate access to compact ports.
- Window to check the condition of the cleaning tape.
- Antistatic resin body with protective cap.
- Identification label on the body: LC/MU, 1.25 mm and more than 800 cleanings.

Technical specifications

Parameter	Specification
Type	One-Click dry cleaner
Ferrule	1.25 mm
Connectors	LC / MU
Nominal cleaning capacity	More than 800 operations
Operation	Manual push operation

Technical specifications

Parameter	Specification
Consumable	Internal cleaning tape; dry use
Material	Antistatic resin
Dimensions	175 × 18 × 18 mm
Extension	Extendable rod with selector
Monitoring	Window to check tape condition
Protection	Protective cap with transparent tether
Color	Dark violet-blue
Reference product weight	0.05 kg
Reference individual packaging	20 × 3 × 3 cm
Reference gross weight	0.10 kg
Pack size	1 piece
Operating sequence	Inspect, clean and inspect again
Warranty	5 years

Applications

LC panels
Connector cleaning in compact spaces.

Optical networks
Inspection and cleaning before connecting or measuring.

Transceiver replacement with LC interface
Clean the patch cord connectors when replacing an optical module and check the end face before reconnecting it.

Patch cord preparation in the workshop
Clean compatible 1.25 mm ferrules before testing and fit clean protection when storing the assembly.

Packaging & contents

1 cleaning pen with protective cap and transparent tether. Reference individual package: 20 × 3 × 3 cm; reference gross weight: 0.10 kg. Connectors and inspection equipment not included.

Warranty

KONGIA 5-year warranty.

Declared compliance

RoHS · ISO 9001 · REACH · CE Compliant