

Standard US PDU, 12 NEMA 5-15R Female Outlets, 19-Inch 1U Rack, Aluminum Alloy Heat-Dissipating Flame-Resistant Antistatic Body, One-Piece Thickened Copper Busbar, Fixed 125V/15A, Overload Protection, 6 FT (1.8 m) 14AWG Pure Copper Cord

Racks & Power / Rack PDUs

KONGIA PDU with 12 NEMA 5-15R outlets, 19-inch 1U rack. Total capacity: 125 V / 15 A / 1875 W. Overload protection; no SPD. Anodized aluminum, flame-retardant PC modules and thickened copper busbar. Pure copper 14 AWG cable, 6 FT (1.8 m). Rack ear mounting; 4 screws included at no extra cost. 5-year warranty.



PDU PARA RACK 1U

12 tomas NEMA 5-15R • Protección de sobrecarga

KG-PDU-12US-15A-1U

Brand
KONGIA

Series
Standard, with overload protection

Output outlets
12 grounded NEMA 5-15R female receptacles, US standard

Key features

- 12 NEMA 5-15R female outlets; 19-inch rack and 1U
- Fixed 125 V / 15 A; 1875 W total; overload protection
- Standard series without surge protection
- Anodized aluminum: heat dissipation, fire resistance and antistatic properties; flame-retardant PC modules
- One-piece thickened copper busbar; pure copper 14 AWG cable, 6 FT (1.8 m)
- Illuminated switch with transparent cover and warning sign
- Rack ear mounting; 4 screws included at no extra cost
- KONGIA 5-year warranty

Technical specifications

Parameter	Specification
Brand	KONGIA
Series	Standard, with overload protection
Output outlets	12 grounded NEMA 5-15R female receptacles, US standard
Format	Standard 19-inch rack, horizontal 1U
Fixed rated voltage	125 V AC
Total rated current	15 A for the entire PDU
Total rated power	1875 W at 125 V / 15 A, shared across all outlets
Overload protection	Integrated circuit breaker
Surge protection	Not included
Housing	Black aluminum alloy with oxidation surface treatment (anodizing); heat dissipation, fire resistance and antistatic properties
Outlet modules	Flame-retardant PC (polycarbonate)
Internal conductor	One-piece thickened copper busbar
Power cable	6 FT (1.8 m), 14 AWG, pure copper, rear exit
Input plug	Grounded NEMA 5-15P
Switch	Illuminated ON/OFF with transparent cover; red triangle and SWITCH COVER wording
Mounting	Rack mounting using mounting ears
Contents	PDU with cable and switch cover; 4 installation screws included at no extra cost
Use	Indoors
Warranty	5 years KONGIA

Applications

Server Racks and Network Rooms

Power for equipment compatible with 125 V, up to 15 A and 1875 W total load.

Offices and Computer Rooms

Mounting using ears in 19-inch racks.

Workshops and Cabinets

Rack installation with four screws included at no extra cost.

Video Surveillance Cabinets

Distribute power between a recorder and network equipment with compatible plugs, calculating the combined load before connecting to the PDU.

Packaging & contents

1 PDU with 14 AWG 6 FT (1.8 m) cable and switch cover; 4 installation screws included at no extra cost.

Warranty

KONGIA 5-year warranty.