

P5200 PRO Rechargeable Touchscreen OTDR · 1310/1550 nm · Up to 100 km

Professional Installations / OTDR & Test Equipment

OTDR for G.652D single-mode fiber · 1310/1550 nm · 24/22 dB · Ranges up to 100 km · 4.3-inch touchscreen · OPM, VFL and RJ45 tests · 5200 mAh battery · USB-C.



OTDR TÁCTIL P5200 PRO

P5200 PRO · 100 km · 1310/1550 nm

Pantalla táctil 4,3" · USB-C · 5200 mAh

Mapa de eventos · OPM · VFL · Pruebas RJ45

KG-FT-OTDR-P5200

KG-FT-OTDR-P5200

Fiber type

Single-mode G.652D

OTDR wavelengths

1310/1550 ±20 nm

Dynamic range

24/22 dB

Key features

- Dual-wavelength single-mode OTDR: 1310/1550 nm.
- Dynamic range of 24/22 dB and test ranges up to 100 km.
- 4.3-inch color touchscreen and physical buttons.
- Dead zones: 1.5 m event and 7 m attenuation.
- Event map, OPM, VFL of at least 10 mW and integrated light source.
- RJ45 cable mapping, length measurement and location.
- Rechargeable 5200 mAh battery and USB-C connection.
- SOR traces, internal memory for at least 1000 records and SD card support.
- LED illumination and carrying case.

Technical specifications

Parameter	Specification
Model	P5200 PRO
Fiber type	Single-mode G.652D
OTDR wavelengths	1310/1550 ±20 nm

Technical specifications

Parameter	Specification
Dynamic range	24/22 dB
Test ranges	100 m / 500 m / 1 / 2 / 5 / 10 / 20 / 40 / 60 / 100 km
Usable reach	Depends on link losses and conditions
Event dead zone	1.5 m
Attenuation dead zone	7 m
Pulse width	5 / 10 / 20 / 50 / 100 / 275 / 500 ns; 1 / 2 / 5 / 10 μ s
Distance accuracy	$\pm(1 \text{ m} + \text{sampling interval} + 0.005\% \times \text{measurement range})$
Linearity	$\pm 0.2 \text{ dB/dB}$
Sampling points	Maximum 20,000
Sampling resolution	0.2–8 m
Loss resolution	0.001 dB
Distance resolution	0.001 m
Refractive index	1.0000–2.0000
Reflectance accuracy	$\pm 3 \text{ dB}$
File format	Standard SOR
Screen	4.3-inch color touchscreen LCD
OPM	–50 to +26 dBm; uncertainty $\pm 5\%$
Calibrated OPM wavelengths	850 / 1270 / 1300 / 1310 / 1490 / 1550 / 1577 / 1625 / 1650 nm
OPM frequency identification	270 / 330 Hz / 1 / 2 kHz
OPM connector	Universal FC/SC/ST
Optical source	Same as OTDR wavelengths; FP-LD laser
Source power	–5 dBm $\pm 2 \text{ dB}$, adjustable; uncertainty $\pm 5\%$
Source modes	CW / 270 / 330 / 1000 / 2000 Hz
Optical connectors	Interchangeable FC/SC/ST
VFL	$\geq 10 \text{ mW}$
Declared laser classification	Class 3B

Technical specifications

Parameter	Specification
RJ45	Wire sequence, length and location
Battery	5200 mAh / 3.7 V
Charging	USB-C
Memory	Internal ≥ 1000 records; supports SD card
Operating temperature	-10 to +50 °C
Storage temperature	-40 to +70 °C
Humidity	0-90%, non-condensing
Dimensions	183 × 107 × 45 mm
Approximate weight	0.5 kg (480-520 g according to supplied references)
Package weight	Approximately 850 g
Package dimensions	Approximately 196 × 128 × 102 mm

Applications

Single-mode link installation

Distance measurement, trace analysis and event map.

Optical fiber maintenance

Loss, connector and splice diagnostics.

Field optical tests

Checks using OPM, light source and VFL.

RJ45 diagnostics

Cable mapping, length and location using receiver and remote module.

Packaging & contents

P5200 PRO OTDR RJ45 locating receiver RJ45 remote module Optical adapter Charger and USB cable Carrying case and strap User manual and box