

Lever Wire Connector, 3-Way, 32 A, 250 V, 50-Pack

Professional Installations / Terminals & Quick Connectors

KONGIA 3-way connector with transparent housing, orange levers, 32 A, 250 V and copper conductor range from 0.08 to 4.0 mm².

CONECTOR DE 3 VÍAS

PARA CABLE RÍGIDO Y FLEXIBLE
Carcasa transparente / conductor de cobre

CORRIENTE NOMINAL	32 A
TENSIÓN NOMINAL	250 V
LONGITUD DE PELADO	10 mm

RANGO DE CABLE

	Rígido / semirrígido 0.08-4 mm ²
	Flexible 0.08-4 mm ²

KG-TERM-LC3 • 3 VÍAS • TRANSPARENTE/NARANJA



KG-TERM-LC3-50

Type

Reusable lever quick connector

Number of ways

3

Rated current

32 A

Key features

- 3 inputs with independent levers
- Rated current of 32 A and rated voltage of 250 V
- Copper conductor range: 0.08-4.0 mm²
- Strip length of 10 mm
- Transparent flame-retardant housing for visual inspection
- Quick-opening orange levers
- Dimensions: 20.5 × 17.0 × 14.5 mm
- Compatible with solid, stranded and flexible copper
- Reusable during installation and maintenance
- Pack of 50 pieces
- Standard documentation: RoHS, REACH SVHC, CE DoC, CNAS and ISO 9001

Technical specifications

Parameter	Specification
Type	Reusable lever quick connector

Technical specifications

Parameter	Specification
Number of ways	3
Rated current	32 A
Rated voltage	250 V
Compatible conductors	Solid, stranded and flexible copper
Cross-section range	0.08–4.0 mm ²
Strip length	10 mm
Dimensions (length × width × height)	20.5 × 17.0 × 14.5 mm
Housing	Transparent and flame-retardant
Levers	Orange, individually operated
Conductive contact	Copper
Reusable	Yes, if free from damage, deformation or overheating
Pack size	50 pieces per package
IP rating	Not declared; install inside a suitable enclosure
Warranty	5 years

Applications

Junction boxes

Joins or branches up to 3 conductors inside a protected enclosure.

Light fixtures

Facilitates compact connections during assembly, replacement and maintenance.

Control panels

Organizes copper conductor distribution with visual inspection.

Electrical installation

Enables extensions and changes without screw connections.

Maintenance

The individual lever allows opening and reconnection when the component is in good condition.

Packaging & contents

50 pieces in KONGIA packaging with SKU and batch identification. Cables, tools, electrical boxes and application accessories not included.

Warranty

KONGIA 5-year warranty. Excludes incorrect selection, out-of-range installation, overload, overheating, use with aluminum, unintended environmental exposure and product modification.

Declared compliance

RoHS · ISO 9001 · REACH · CE Compliant · CNAS